



SPECIFICATIONS

Product Description: **D-2 MOLD LITE SAMPLER**
Part Number: **9800-88**
Style: **DIAPHRAGM**

GENERAL DESCRIPTION:

This low maintenance oscillating pump is designed for use with all mold sampling cassettes and impactors. It is lightweight, quiet performance, and easy to use. It has a built in adjustable flow meter/regulator and rubber suction cup feet to prevent the pump from moving while in use. The pump is available as a kit (P/N 9800) with an adjustable tripod stand.

CONSTRUCTION:

- Rigid metal housing
- Powder coated (Gray color)
- Built in plumbing
- Adjustable flow meter/ regulator
- Built in handle
- Rubber suction cup feet
- On/Off Switch on handle – Less breakage

PUMP:

Type: Oscillating Double Diaphragm
Performance: 3-33 LPM (liters per minute)

MOTOR:

Specs: 115 VAC, Single Phase, 60 Hertz, .45 Amps
Inlet Filter: 40.0 Micron bronze/steel
Cord: 6.5' 105°C, 18 AWG
Switch: ON/OFF Switch built into handle
Plug: Integrated NEMA 5-15

OPTIONAL:

Tripod Stand: Anodized aluminum, adjustable with 3 extending rods.
(P/N: **9804-08**) Available as a kit (P/N: **9800**) with pump and stand.



DIMENSIONS:

Length	Width	Height	Weight
6"	6"	6.25"	5.3 lbs