



FIND IT! WITH SENSIT[®] GOLD

VERSATILE GAS DETECTION INSTRUMENTS
*Sensit[®] Gold is designed to provide personal protection
from potentially hazardous conditions and help
find the source of combustible gases fast!*



Sensit[®] Gold Features

- Highly Sensitive Leak Detection
- Display up to 4 gases
 - ▶ LEL (Optional PPM and % Volume)
 - ▶ Oxygen
 - ▶ Carbon Monoxide
 - ▶ Hydrogen Sulfide
- Internal Pump
- Infrared Downloading
- Lowest Cost, Long Life Sensors
- LED Warning Lights
- Bright LCD Display
- Optional Air Free CO Test



Sensit[®] Gold Instruments, simply the best value!

FIND IT! WITH SENSIT® GOLD

Whether you need an investigation tool or a confined space monitor - you can depend on the Sensit® Gold to provide the safety and accuracy you need.

STANDARD FEATURES

- Internal Pump
- Water/Dust Filter
- Push Button Operation
- Field Calibration
- Date/Time Display
- Calibration Alert
- Operation Memory
- Calibration Memory
- Infrared Download
- Audible/Visual Alarms
- Backlit LCD
- Hard Carrying Case
- Programmable Auto Shut Off

SENSING FEATURES

SENSIT® GOLD INSTRUMENTS	LEL ALARMS	LEL DISPLAY	100% GAS	LEAK DETECTION	CARBON MONOXIDE	OXYGEN	HYDROGEN SULFIDE
SENSIT EX SG00500-A	•	•		•			
SENSIT EX-CO SG00500-B	•	•		•	•		
SENSIT EXPlus SG00500-C	•	•		•		•	
SENSIT EX-COPlus SG00500-E	•	•		•	•	•	
SENSIT EX-TOX SG00500-D	•	•		•			•
SENSIT EX-TOXPlus SG00500-G	•	•		•		•	•
SENSIT 4GAS SG00500-H	•	•		•	•	•	•
SENSIT GOLD 100 SG00900	•	•	•	•	•	•	•

OPTIONS

- Recharger Kit
- Printer
- PC Interface
- Hot Air Probe
- Confined Space Kit
- Calibration Kit



Sensit® Gold instruments are Approved UL913, For Class 1, Division 1, Groups C and D Hazardous locations when used with alkaline batteries.



Other Sensit® Gold versions available:
 • Sensit® Gold 100 - 100% Gas Volume
 • Sensit® Gold CSE - Confined Space Monitor

SENSOR SPECIFICATIONS

TYPE	RESOLUTION	RANGE	ACCURACY
Leak	N/A	0 -50,000ppm	N/A
PPM	10ppm	0-2000ppm	N/A
LEL	0.1%	0-100%	±10%
%Gas	0.1%	5-100%	±5%
O ₂	0.1%	0-25%	±0.2% or 2%*
CO	1ppm	0-2000ppm	±5ppm or 5%*
H ₂ S	1ppm	0-100ppm	±1ppm or 5%*

PRODUCT SPECIFICATIONS

Size: 11.5" x 3" x 2.32" (292 x 76 x 69 mm)
 Weight: 1.2 Lbs.
 Operational Temp: 0 to 120° F
 Storage Temp: -20 to 132° F
 Battery Life: Alkaline - 16 Hrs. continuous

APPLICATIONS

- Gas Leak Survey/Investigations
- Confined Space Monitoring
- Gas Emergency Investigations
- Vessel Testing

USERS

- Utilities
- Maintenance
- Fire Departments
- Safety Inspectors
- Home Inspectors
- Water/Sewer Departments
- Heating Contractors
- Utility Contractors
- Industrial Plants
- Propane Marketers

FOR MORE INFORMATION

J And N Enterprises, Inc.
 851 Transport Drive
 Valparaiso, IN 46383-8432
 Phone: (888) 4SENSIT
 (473-6748)
 (219) 465-2700
 Fax: (219) 465-2701
 www.gasleaksensors.com



Distributed by _____