

WARRANTY EXCLUSIONS AND LIMITATION OF LIABILITY

IF THE USER DOES NOT ACCEPT THE FOLLOWING TERMS, THE USER SHOULD NOT USE THE SAFEAIR BADGES AND COLOR COMPARATORS.

Seller warrants that, for the lesser of one (1) year or the shelf-life provided on the Seller's product, its packaging or its literature, its products shall conform to the description of such products as provided on the Seller's product, its packaging or its literature. THIS WARRANTY IS EXCLUSIVE, AND SELLER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Seller's warranties made in connection with this sale shall not be effective if Seller has determined, in its sole discretion, that Buyer has misused the products in any manner, has failed to use the products in accordance with safe industry standards and practices, or has failed to use the products in accordance with Seller's written operating instructions, or other instructions furnished by Seller to Buyer.

Seller's sole and exclusive liability and Buyer's exclusive remedy with respect to products to Seller's satisfaction to be defective or nonconforming shall be replacement of such products without charge or refund of the purchase price, in Seller's sole discretion, upon the return of such products in accordance with Seller's instructions. All claims must be brought within one (1) year of shipment, regardless of their nature.

SELLER SHALL NOT IN ANY EVENT BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES OF ANY KIND RESULTING FROM ANY USE OR FAILURE OF THE PRODUCTS, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE INCLUDING, WITHOUT LIMITATION, LIABILITY FOR LOSS OF USE, LOSS OF WORK IN PROGRESS, DOWN TIME, LOSS OF REVENUE OR PROFITS, FAILURE TO REALIZE SAVINGS, LOSS OF PRODUCTS OF BUYER OR OTHER USE OF ANY LIABILITY OF BUYER TO A THIRD PARTY ON ACCOUNT OF SUCH LOSS, OR FOR ANY LABOR OR ANY OTHER EXPENSE, DAMAGE OR LOSS OCCASIONED BY SUCH PRODUCT INCLUDING PERSONAL INJURY OR PROPERTY DAMAGE UNLESS SUCH PERSONAL INJURY OR PROPERTY DAMAGE IS CAUSED BY SELLER'S GROSS NEGLIGENCE.

Warning: Keep out of reach of children, if ingested seek medical attention immediately.



2557 Production Rd.
Virginia Beach, VA 23454
Phone: (757) 431-2260 Fax: (757) 216-6209
E-mail: customerservice@morphtec.com

©1997, Morphix Technologies®
Publication Number: KM4-4A.8-0307
US Patent Number: 6,284,198



**Operating Instructions For
Carbon Dioxide Monitor
(Part Number: 382017)**

Technical Summary

Physical Specifications:

Dimensions	(74 ± 1 mm) x (41 ± 1 mm) x (1 mm)
Weight	1.5 g
Refrigerated shelf life	1 year
Color change	olive green to burnt orange

Sampling Parameters:

Exposure level	
Badge	8,000 ppm-hr,
Badge with color comparator	1,800 - 80,000 ppm-hr
Minimum detectable limit (8 hours)	1,000 ppm
Maximum recommended sampling time	10 hours
Minimum recommended sampling time	15 minutes
Relative humidity range	10% - 83%
Face velocity range	5 - 168 cm/sec
Temperature range	50°F - 95°F
Mean coefficient of variation	±8.49
Bias at ambient conditions	-2.67%
Light effect – UV (direct sunlight)	not recommended
Light effect – visible	no effect
Color stability	2 days

Applications:

The SafeAir carbon dioxide badge may be used for personnel or area monitoring for exposure times ranging from 15 minutes to 10 hours. For higher resolution, the SafeAir carbon dioxide badge may be used with the SafeAir carbon dioxide color comparator (part number: 383009).

Cross Interferences:

The SafeAir carbon dioxide badge was treated in atmospheres containing at least two times the OSHA PEL for the following substances: alcohols, aromatic hydrocarbons, halogenated hydrocarbons, aldehydes, carbon monoxide, ammonia and hydrogen chloride. These substances showed no effect on the performance of the SafeAir carbon dioxide badge. No other interferences are known.

Öz dâ cãã KEOÁQc!} æñ } æñ & ÁÁUÁÓ[çÁ JI ÁÁO^T [ç ÊÖ Á Î HFÉÁÁ €€Í GÈGHÁÁG FJÈÌ Ì ÈÌ Í ÁÁæÁG FJÈÌ Ì ÈÌ Í ÁÁæÁ • Á æ& dÈ [{

Introduction

Carbon dioxide is a colorless gas. It may be sold in cylinders as a compressed, liquefied gas. Man-made sources of carbon dioxide come mainly from the burning of various fossil fuels for power generation and transport use. Potential health effects from long term and/or high concentration exposure to carbon dioxide include nasal and respiratory tract irritation, central nervous system effects, dizziness, drowsiness, blurred vision, fatigue, nausea, headache, loss of reflexes, seizures, loss of consciousness, coma, respiratory arrest and sudden death. This may also cause irregular heart rhythm. Repeated or prolonged exposure may cause behavioral changes.

The OSHA exposure limit for carbon dioxide is 5000 ppm (TWA). The NIOSH exposure limit for carbon dioxide is 30000 ppm (STEL) and 5000 ppm (TWA) 10 hours.

Principle of Operation

The SafeAir carbon dioxide badge is a monitoring system designed to indicate the presence of carbon dioxide at concentrations below the permissible exposure limit. The SafeAir carbon dioxide badge detects the presence of carbon dioxide by forming a color change in the shape of a triangle inside an olive green frame. This indication is produced by a color-forming reaction, which occurs when carbon dioxide reacts with a flat indicator layer.

Operating Instructions

1. Remove the pouch from the refrigerator and allow it to warm to room temperature.
2. Remove the badge from its protective pouch.
3. Remove color standard from its pouch and attach together with the badge to the clip. The color standard should hang on the back of the badge with the color side facing away from the badge
4. For personnel monitoring, attach the badge near the user's breathing zone (i.e. the collar) with the front side exposed to the surrounding atmosphere.
5. For area monitoring, attach the badge to a stand and mount in a centralized area with the front side exposed to the surrounding atmosphere.
6. The color change will appear inside the triangle on the side facing the body.
7. At the end of the exposure period, **return the badge to its original pouch and let stand for 1 hour at room temperature to allow complete development of color. Retain the color standard.**
8. When the color change matches the attached color standard, the dose is 8000 ppm-hr.
9. To obtain the average concentration, divide the exposure dose (ppm-hr) by the exposure time in hours (hr).

Storage

The SafeAir carbon dioxide badge should be refrigerated in its sealed bag at all times.

Benefits

1. **Accurate Detection:** The SafeAir carbon dioxide badge is designed to react selectively with carbon dioxide with minimum interference from other substances.
2. **Applications:** The SafeAir badge may be used for personnel screening and for area monitoring or area mapping.
3. **Ease of Use:** The SafeAir badge is a direct-read device that gives immediate, on-site results.

Other Available Monitors

1. **SafeAir Badges:**

Ammonia	Dimethyl Amine	Mercury
Aniline	Formaldehyde	Nitrogen Dioxide
Aromatic Isocyanates	Hydrazine	Ozone
Carbon Monoxide	Hydrides	Phosgene
Chlorine	Hydrogen Chloride	Sulfur Dioxide
Chlorine/Chlorine Dioxide	Hydrogen Sulfide	UDMH
2. **SafeAir Color Comparators:**

Arsine ¹	Hydrogen Chlorine	TDI ⁴
Chlorine	MMH ³	UDMH
Chloroformates ²	Phosgene	
Diborane ¹	Phosgene ext. range	
Hydrazine	Phosphine ¹	

If you require SafeAir monitors for a chemical hazard not listed, please contact Morpox Technologies® for a free compound consultation at (800) 808-2234.

¹ To be used with the SafeAir hydrides badges

² To be used with the SafeAir phosgene badges

³ To be used with the SafeAir hydrazine dual level badges

⁴ To be used with the SafeAir aromatic isocyanates badges